

LONDON FOGGERS

Used everywhere in the world
since 1968

MODEL 9-10 High Output ULV Aerosol Generator



**PISTOL GRIP
CAB CONTROL**

**WIRELESS
CONTROLLER**



**HOOT
NOZZLE**

Standard Features on the 9-10

- Teflon coated aluminum HOOT nozzle
- Pistol grip cab control start - spray - formulation - flush functions
- FMI formulation pump, 3/8" ceramic piston
- Triple V Belt drive
- Kohler single cylinder OHV command engine
- Silencer tube

Optional Features on the 9-10

- 1 or 2 years spares kits
- Tachometers / Hour meter
- GPS, tracking & recording features
- Additional capacity gas tank

The NEW 9-10 ULV sprayer (9HP -10 MPH) built by London Foggers was designed as an update to the XKE machine, and at the request from industry for a more affordable blower machine than London Foggers model 18-20. It has been extensively tested in the field prior to its release and is fully backed by an iron clad warranty. The ability of this machine to share a majority of parts used by our best selling model 18-20 will surely mean this machine will take no getting used to. The reliability of the 18-20 is literally built into this machine from the ground up.

Next to reliability, the number one thing of importance in a sprayer is efficiency, and the 9-10 is second to none. The 9-10 will fully meet label specifications on 90% of mosquito adulticide labels at 10MPH++ as this machine uses a solid aluminum nozzle, with zero moving parts, which is then Teflon coated to increase life. The complex aluminum nozzle design on the 9-10 has shown in independent testing to be far more repeatable, easier to calibrate, and create a better droplet dispersion than ANY OTHER SPRAYER ON THE MARKET. Standard features on the 9-10 pistol grip cab control are a main power switch, engine start switch, and spray / flush tank selector switch.

The 9-10 will fully work with our wireless remote, and our "London Flow" GPS variable flow system, which will plug and play into at least 5 popular off the shelf programs currently in use today. This will allow the 9-10 to fully comply with all NPDES requirements seamlessly, regardless of which technology system is in use at your location.

Specifications

Engine	9.5 HP overhead valve single cylinder, electric start
Formulation Pump	12 Volt DC adjustable output, positive displacement, 0-20 oz./min
Formulation Tank	15 gallon (56 liters), corrosion resistant
Particle Size	80% of droplets-less than 20 microns
Fuel Tank	1.5 gallon (28.38 litre) with gauge
Flush Tank	1 1/2 quart (1.43 liter) corrosion resistant
Blower	Rotary Lobe Positive Displacement 181 CFM @ 3600 RPM
Weight	355 lbs (152 kg)
Length	37" (94 cm)
Width	46" (117 cm)
Height	39" (99 cm)

**505 Brimhall Avenue
Long Lake, MN 55356**

P. 952-473-5366

F. 952-473-5302

TF. 800-448-8525

E. salesupport@londonfoggers.com



**Sentinel
GPS**



*Used everywhere
in the world*

www.londonfoggers.com

© Copyright London Foggers All Rights Reserved