

# LONDON FOGGERS

WORLDWIDE VECTOR CONTROL SINCE 1968

## MODEL 9-10

High Output ULV Aerosol Generator

The **9-10** ULV fogger (9.5HP -10 MPH) built by London Foggers was designed as an update, at the request from industry, for a more affordable blower machine than the London Foggers Model 18-20. It has been extensively tested in the field prior to its release and is fully backed by an iron clad warranty. The ability of this machine to share a majority of parts used by our best selling Model 18-20 will surely mean this machine will take no getting used to. The reliability of the 18-20 is literally built into this machine from the ground up.

Next to reliability, the number one thing of importance in a sprayer is efficiency, and the **9-10** is second to none. The **9-10** will meet label specifications of mosquito adulticide labels at 10MPH. This fogger uses a solid aluminum nozzle with moving parts. The complex aluminum nozzle design on the **9-10** has been shown in independent testing to be far more repeatable, easier to calibrate, and create a better droplet dispersion than ANY OTHER FOGGER ON THE MARKET. Standard features on the **9-10** pistol grip cab control are a main power switch, engine start switch, and spray / flush tank selector switch.

The "London Flow" GPS variable flow system, which will plug and play into at least 5 popular off the shelf programs currently in use today.

### Standard Features on the 9-10

- Aluminum nozzle, rotates 360°
- Pistol grip cab control start - spray - formulation - flush functions
- FMI formulation pump, 3/8" ceramic piston
- Triple V Belt drive
- Kohler single cylinder OHV command piston
- Silencer tube

### Optional Features on the 9-10

- 1 or 2 Year Spare Parts Kits
- Tachometers / Hour meter
- GPS, flow control



360°  
ALUMINUM  
NOZZLE



PISTOL GRIP  
CAB CONTROL

### Specifications

Engine	9.5 HP overhead valve single cylinder, electric start
Formulation Pump	12 Volt DC adjustable output, positive displacement, 0-20 oz./min
Formulation Tank	15 gallon (56 liters), corrosion resistant
Particle Size	80% of droplets-less than 20 microns
Fuel Tank	1.5 gallon (28.38 litre) with gauge
Flush Tank	1 1/2 quart (1.43 liter) corrosion resistant
Blower	Rotary Lobe Positive Displacement 181 CFM @ 3600 RPM
Weight	355 lbs (152 kg)
Length	37" (94 cm)
Width	46" (117 cm)
Height	39" (99 cm)



P. 952-473-5366

F. 952-473-5302

TF. 800-448-8525

E. [salesupport@londonfoggers.com](mailto:salesupport@londonfoggers.com)

505 Brimhall Ave. P.O. BOX 406 - Long Lake, MN 55356

[www.londonfoggers.com](http://www.londonfoggers.com)

© Copyright London Foggers All Rights Reserved